

Serial No. 10/633,088
Attorney Docket No. 35165552.13

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

1. (Currently Amended) A toilet apparatus comprising:
 - a) a base portion having a width of about 21.5 inches and a length of about 29.05 inches, wherein the base portion further comprises a reinforced portion comprising a plurality of ceramic walls vertically extending from a bottom of the base portion to the bowl portion;
 - b) a bowl portion attached to the base portion wherein the width of the outer portion of the bowl is about 25 inches, the length of the outer portion of the bowl is about 32 inches, and wherein the outer portion of the bowl is substantially aligned with a bottom of the base portion;
2. ~~(Cancelled) A toilet apparatus of Claim 1 wherein the base portion further comprises a reinforced portion comprising a plurality of ceramic walls extending from a bottom of the base portion to the bowl portion.~~
3. (Currently Amended) A toilet apparatus of Claim 2 1 wherein the reinforced portion is aligned with an anchorage point operable to attach the toilet apparatus to a flat surface.
4. (Original) A toilet apparatus of Claim 3 further comprising a plurality of anchorage points and a corresponding plurality of reinforced portions.
5. (Original) A toilet apparatus of Claim 4 wherein two anchorage points and two corresponding reinforced portions are located on opposite sides of the base portion.

Serial No. 10/633,088
Attorney Docket No. 35165552.13

6. (Original) A toilet apparatus of Claim 5 wherein the two anchorage points are located about 8.95 inches from a line bisecting the toilet apparatus into symmetrical left and right sides.

7. (Currently Amended) A toilet apparatus of Claim 2 1 wherein a width of the reinforced portion is about 2.9 inches and a length of the reinforced portion is about 2.4 inches.

8. (Original) A toilet apparatus of Claim 1 wherein a thickness of a wall of the base portion is at least about .39 inches.

9. (Original) A toilet apparatus of Claim 1 wherein the height of the toilet apparatus is greater than about 17 inches.

10. (Currently Amended) A toilet seat comprising
- a) an inner and an outer rim;
 - b) two vertically extending rigid members located between the outer and inner rims of the left side and the right side of the toilet seat, wherein the vertically extending rigid members are positioned for alignment with an interior edge of a toilet bowl as to prevent lateral displacement of the seat when in use and wherein the vertically extending rigid members are integral to the seat.

Serial No. 10/633,088
Attorney Docket No. 35165552.13

11. (Original) A toilet seat of Claim 10 wherein a width of the toilet seat is about 25 inches and a length of the toilet seat is about 24.5 inches.
12. (Original) A toilet seat of Claim 10 wherein a width of an aperture formed by the inner rim of the toilet seat is less than about half the width of the toilet seat.
13. (Original) A toilet seat of Claim 10 wherein a length of the aperture formed by the inner rim of the toilet seat is greater than about two-thirds the length of the toilet seat.
14. (Currently Amended) A toilet seat of Claim 10 wherein a width of the aperture formed by the inner ~~portions~~ rim of the toilet seat is about 8.2 inches and a length of the aperture formed by the inner ~~portions~~ rim of the toilet seat is about 16.7 inches.
15. (Original) A toilet seat of Claim 10 further comprising a plurality of radially disposed support members on a bottom surface of the toilet seat.
16. (Currently Amended) A toilet comprising:
- a) a base portion having a width of about 21.5 inches and a length of about 29.05 inches, wherein the base portion further comprises a reinforced portion comprising a plurality of ceramic walls vertically extending from a bottom of the base portion to the bowl portion;
 - b) a bowl portion attached to the base portion wherein the width of the outer portion of the bowl is about 25 inches, the length of the outer portion of the bowl is about 32 inches, and

Serial No. 10/633,088
Attorney Docket No. 35165552.13

wherein the outer portion of the bowl is substantially aligned with a bottom of the base portion;
and

c) a toilet seat comprising an inner and an outer rim and further comprising two vertically extending rigid members located between the outer and inner rims of the left side and the right side of the toilet seat, wherein the vertically extending rigid members are positioned for alignment with an interior edge of a toilet bowl as to prevent lateral displacement of the seat when in use and wherein the vertically extending rigid members are integral to the seat.

17. (Cancelled) ~~A toilet of Claim 16 wherein the base portion further comprises a reinforced portion comprising a plurality of ceramic walls extending from a bottom of the base portion to the bowl portion.~~

18. (Currently Amended) A toilet of Claim ~~17~~ 16 wherein the reinforced portion is aligned with an anchorage point operable to attach the toilet apparatus to a flat surface.

19. (Original) A toilet of Claim 18 further comprising a plurality of anchorage points and a corresponding plurality of reinforced portions

20. (Original) A toilet of Claim 19 wherein two anchorage points and two corresponding reinforced portions are located on opposite sides of the base portion.

21. (Original) A toilet of Claim 20 wherein the two anchorage points are located about 8.95 inches from a line bisecting the toilet apparatus into symmetrical left and right sides.

Serial No. 10/633,088
Attorney Docket No. 35165552.13

22. (Currently Amended) A toilet of Claim 17 16 wherein a width of the reinforced portion is about 2.9 inches and a length of the reinforced portion is about 2.4 inches.

23. (Original) A toilet of Claim 16 wherein the thickness of a wall of the base portion is at least about .39 inches.

24. (Original) A toilet of Claim 16 wherein a width of the toilet seat is about 25 inches and a length of the toilet seat is about 24.5 inches.

25. (Original) A toilet of Claim 16 wherein a width of an aperture formed by the inner rim of the toilet seat is less than about half of a width of the toilet seat.

26. (Original) A toilet of Claim 16 wherein a length of the aperture formed by the inner rim of the toilet seat is greater than about two-thirds of a length of the toilet seat.

27. (Currently Amended) A toilet of Claim 16 wherein a width of the aperture formed by the inner ~~portions~~ rim of the toilet seat is about 8.2 inches and a length of the aperture formed by the inner ~~portions~~ rim of the toilet seat is about 16.7 inches.

28. (Original) A toilet of Claim 16 further comprising a plurality of radially disposed support members on a bottom surface of the toilet seat.

Serial No. 10/633,088
Attorney Docket No. 35165552.13

29. (Original) A toilet of Claim 16 wherein the height of the toilet is greater than about 17 inches.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.